

# Emergency Network Intercom with Hidden CMOS IP Camera



## Future-proof Technology

The Telexper Emergency Intercom is a 2-way communication device which enables user to commute to the Network Commander Station (or nCS) in the security center immediately after pressing the Big Red Panic button. Built-in hidden CMOS Camera allows the security center to see and communicate with the user on-site.


It is implemented with Internet Protocol (IP) and is designed particularly for surveillance and safety, public and private. It can also be used for remote intercom and monitoring applications which allows the user to view their cameras through an Internet connection from a computer or a 3G phone.

It provides around-the-clock, high quality H.264 video with Internet Protocol which is used for communicating data over TCP/IP.



## Features:

- Big red panic button input for emergency intercom
- 2-way audio communication over IP networks with Echo Cancel feature
- 1/3" CMOS Sensor
- PoE (IEEE802.3af, Power-over-Ethernet)
- H.264/M-JPEG (SOC) dual-mode compression
- Built-in hardware motion detection
- Camera Resolution of 1280x720 @30fps
- User-friendly GUI and no configuration is required



2mm thick, 2.05 KG, 150\*102\*250mm (H\*W\*L)

## Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F.-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: [sales-tw@telexper.com](mailto:sales-tw@telexper.com)

## Specification

Model	nEI
Panic Button	Big Red Color
Audio Codec	PCM,ADPCM
2-Way Audio	Yes, (Microphone x 1, Speaker x 1)
Audio Echo Cancel	Yes
Image Sensor	1/3" CMOS Sensor
Resolution & Rate	1280x720 (30fps)
Video Codec	H.264/M-JPEG hardware (SOC) compression
Video Stream	H.264, Multiple Streams
Video Bit Rate	30K- 4M bps
Sensitivity	0.25 Lux / F2.0 / 50 IRE
S/N Ratio	> 48 dB
Electronic Shutter	1/60(1/50) to 1/10,000 sec.
Flicker less	Yes, 1/120 sec.(60Hz) 1/100 sec.(50Hz)
Exposure	Automatic
Back Light Compensation	Automatic
AGC	Automatic
White Balance	Automatic
Motion Detection	Yes, 4 different areas (hardware)
Picture Resolution	1280x720
Lens	Hidden Lens
Video Adjust	Contrast, Brightness, Saturation, Sharpness
Control Output	NO / NC
Control Range	2A 30VAC, 1A 125 VAC, 0.5A 220VAC
Operation System	Linux Embedded
Processor	ARM 9 ,32 bit RISC
Security	Password
Firmware Upgrade	Yes, Remotely
Watch Dog Timer	Yes
Network Interface	RJ-45 (10/ 100 Base-T)
Power Requirement	PoE (IEEE802.3af) or +12V at 1A
Power Consumption	5W
Operating Temperature	-10°C to 50°C, 14°F to 122°F
Operation Humidity	5%--95%
Storage	-30°C to 70°C, -22°F to 158°F
Dimension (L x W x H)	188 x 78 x 1.4 mm + 154 x 56 x 60mm
Software SDK	Yes

TMSP: Telexper Multiple Stream Protocol

(Specifications subject to change without prior notice)

### Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F.-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: sales-tw@telexper.com