

# 3i CCTV

iP, integration, intelligent



Network Video Server

### Features:

- Upgrade any Traditional Analogue Camera to the IP System
- H.264 & M-JPEG Dual-type Codec
- De-centralized & Modularized Design
- Unlimited Number of Camera Expansion at any time
- No Power Cable to Camera Required
- Reduce minimum 50% of Installation Cost
- Less Maintenance Cost than Analogue System
- Up to 30fps @D1, 120fps@CIF (4ch only) Display & Recording
- Multi Video Audio Streaming Design


### Other Componentets of Telexper IP System:

- Network Gigabit PoE Hub ( nHub series)
- Network Hybrid DVR (nHybrid Sereis)
- Network Commander Station ( nCS series)
- Network Matrix Decoder (nMD series)
- Network CMS software (nCMS series)
- Network Video Recoder (nVR series)


### Technology:



### File Size:



### Video Quality:



### Model no

nVS-1  
nVS-1P  
nVS-4QP

### Standard:

IEEE820.3i  
IEEE802.3u  
IEEE802.3af

### Interface:

Video input

1ch  
4ch

RS485

Audio Input/ Ouput

Alarm Input

Control Output

Power to camera

External Power Input

LAN Port

### Video & Audio:

Video format

Video Codec

Video/ Audio stream

Motion Detection

Web Server

Hardware Watchdog

### Power Requirement:

Built-in PD Device

Effective Distance

External Power Input

Power to Camera

### Mechanical:

Enclosure

Installation

Dimension & Weight

1ch

4ch

### Environment:

Operating

Storage

Approvals

1ch Video Server

1ch Video Server built-in PoE

4ch Video Server built-in PoE

10Base-T, 10Mbit/s

100Base-T, 100Mbit/s

Power over Ethernet (PoE)

x 1 (BNC)

x 4 (BNC)

x 1 (terminal)

x 1 (terminal, each, mono)

x 1 (terminal)

x 1 (terminal)

x 1 (terminal)

x 1 (terminal)

x 1 (RJ-45)

works with either NTSC or PAL analogue cameras

H.264 & M-JPEG video stream

up to 30 fps @D1 (all models), 120fps @CIF (4ch only)

built-in

built-in

built-in

Yes (IEEE802.3af)

100m long (away from PoE HUB)

DC12V, 1A(min)

DC12V, 8W (max, for 1ch PoE only)

Aluminum material

Wall mount (Bracket supplied)

99 x 76 x 33 mm, < 300g

120 x 101 x 33 mm, <400g

0 to 50 °C, 10% to 80% R.H. (non-condensing)

(-)10 to (+) 70 °C, 5% to 95% (non-condensing)

(non-condensing)

CE, FCC, RoHS