

# Full HD 5MP IP Bullet Camera, Indoor/Outdoor



## Future-proof Technology

The IP cameras series with mechanical IR cut and day/night capability supports color at day and black & white at night. This all-in-one-design camera series are very versatile. It supports PoE (Power over Ethernet), so there is no need for external power supply. Options of fixed lens, manual and zoom vari-focal are available for different environments. The outdoor model has IP66 Weather-proof protection housing.

It provides round-the-clock, high quality H.265 video with Internet Protocol. Its remote monitoring applications allow homeowners and businesses to view their camera(s) through any internet connection available through a computer or a 3G phone.

## Features:

- 1/2.7" CMOS Progressive Scan
- Resolution of 2592x1944 @20fps
- PoE (IEEE802.3af, Power over Ethernet)
- True Day and Night (Mechanical IR Cut Filter, IR LED)
- Supports Manual Vari-Focal and Zoom lens
- H.265/H.264/MJPEG (SOC) Video compression
- Alarm input x 1
- Two-way audio communication over IP networks
- Multi-streaming
- Built-in hardware motion detection
- Metal Aluminum housing
- Excellent heat dissipation
- User-friendly GUI and no configuration is required
- IP66 weather-proof protection housing
- Local SD Card Storage (optional)
- High power IR LED

Built-in PoE  
IR LEDs  
Multiple Streams  
IP66 Housing




Optional Bracket



Outdoor Model



Local SD Card Storage (optional)



## Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F.-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: sales-tw@telexper.com

## Specification

Model	Indoor	nCam-N1134/xx	nCam-N1144/xx
	Outdoor(IP66)	nCam-N1136/xx	nCam-N1146/xx
Image Sensor	1/2.7" CMOS Progressive Scan		
Resolution & Rate	2592x1944 @20fps		
Video Codec	H.265/H.264/MJPEG hardware (SOC) compression		
Video Stream	H.265/H.264, Multiple Streams		
Video Bit Rate	30K- 6M bps		
Sensitivity	0.1 Lux @ F1.4 (IR LED off) / 0 Lux @ F1.4 (IR LED On)		
S/N Ratio	> 63 dB		
Electronic Shutter	1/5 to 1/30000 sec.		
Flickeress	Yes, 1/120 sec.(60Hz) 1/100 sec.(50Hz)		
Exposure	Automatic		
Back Light Compensation	Automatic		
AGC	Automatic		
White Balance	Automatic		
Motion Detection	Yes, 4 different areas (hardware)		
Picture Resolution	2592x1944		
Lens	Manual Vari-Focal 2.8 mm ~ 12 mm		Zoom Lens 2.7 mm ~ 12 mm
	Video Adjustment Contrast, Brightness, Saturation, Sharpness		
Day/Night	Yes, Mechanical IR Cut Filter		
IR Led	High Power IR LED x 2		
IR Sensitivity	700nm to 1100nm		
IR Distance	20 meters		
GPIO	Alarm in x 1		
Control Interface	RS-485		
2-Way Audio	Yes, (Audio In x1, Audio Out x1)		
Operation System	Linux Embedded		
Processor	ARM 9 ,32 bit RISC		
Security	ID / Password		
Firmware Update	Yes, Remotely		
Watch Dog Timer	Yes		
Network Interface	RJ-45 (10/100 Base-TX)		
Protocol	HTTP, TCP/ IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, RTSP/RTP, TMSP		
Power Requirement	PoE (IEEE802.3af) or 12VDC		
Power Consumption	9W with Higher Power Led ON	9.5W with Higher Power Led ON	
Operating Temperature	-10°C to 50°C, 14°F to 122°F		
Operation Humidity	5%--95%		
Storage	-30°C to 70°C, -22°F to 158°F		
Dimension (L x W x H)	Indoor	Camera Body: 193 x 77 x 76 mm	Aluminum Sunshield: 207 x 83 x 80.5 mm
	Outdoor	Camera Body: 210 x 77 x 76 mm	Aluminum Sunshield: 237 x 83 x 80.5 mm
Weight	Indoor: 880 g Outdoor: 1.15 kg		
Certifications	CE, FCC, RoHS		

TMSP: Telexper Multiple Stream Protocol  
(Specifications subject to change without prior notice)

### Telexper International Inc.

33235 Transit Avenue, Union City, CA 94587 USA / Phone: 1-510-477-9150 / Fax: 1-510-477-9634

3F.-3, No.2, Jian 8th Rd., Zhonghe Dist., New Taipei City 235, Taiwan (R.O.C.) / Phone: +886-2-6620-5898 / Fax: +886-2-6620-6909 / <http://www.telexper.com> / E-mail: sales-tw@telexper.com